

KUŽELOVÉ STOPKY VYMĚNITELNÉ EXCHANGEABLE TAPER SHANKS REPLACEABLE ESPIGAS CÓNICAS REEMPLAZABLES

VK	Kód Code Código	Popis Description Descripción	Náčrt Drawing Croquis	D [mm]	X [mm]	Scales	Scales											
							Vhu 36	Vhu 56	Vhu 80	Vhu 110	Vhu 125	Vhu 160	Vh 70	Vh 110	Vh 140	Vhs 90, 10-125	Vhs 40-180	
VK 360	208.015	MK2-M8 DIN 228A		70	13	0,35	•											
VK 360	208.022	MK2-M10 DIN 228A		70	13	0,35	•											
VK 360	208.039	MK2-3/8"-16 UNC		70	13	0,35	•											
VK 360	208.060	MK3-M10 DIN 228A		70	13	0,46	•											
VK 360	208.077	MK3-M12 DIN 228A		70	13	0,46	•											
VK 360	208.084	MK3-1/2"-12 UNC		70	13	0,46	•											
VK 360	208.121	MK4-M14 DIN 228A		70	14,5	0,75	•											
VK 360	208.138	MK4-M16 DIN 228A	70	14,5	0,75	•												
VK 360	208.145	MK4-5/8"-11 UNC	DIN 1806, ISO 296-63, ČSN 220424	70	14,5	0,75	•											
VK 801	208.510	MK4-M14 DIN 228A		110	18,5	1,35		•	•	•								
VK 801	208.527	MK4-M16 DIN 228A		110	18,5	1,35		•	•	•								
VK 801	208.534	MK4-5/8"-11 UNC		110	18,5	1,35		•	•	•								
VK 801	208.572	MK5-M16 DIN 228A		110	18,5	2,29		•	•	•	•							
VK 801	208.589	MK5-M20 DIN 228A		110	18,5	2,29		•	•	•	•							
VK 801	208.596	MK5-3/4"-10 UNC		110	18,5	2,29		•	•	•	•							
VK 801	208.633	MK6-M20 DIN 228A		110	20	4,74		•	•	•	•							
VK 801	208.640	MK6-M24 DIN 228A	SPECIAL *	110	20	4,74		•	•	•								
VK 801	208.664	MK6-1"-8 UNC	110	20	4,74		•	•	•	•								
VK 360	208.053	MK3-DIN 1806		70	13	0,47	•											
VK 360	208.114	MK4-DIN 1806		70	14,5	0,77	•											
VK 360	208.169	MK5-DIN 1806		70	14,5	1,5	•											
VK 360	208.176	MK6-DIN 1806		70	38	4,16	•											
VK 801	208.503	MK4-DIN 1806		110	18,5	1,47		•	•	•								
VK 801	208.565	MK5-DIN 1806		110	18,5	2,45		•	•	•	•							
VK 801	208.626	MK6-DIN 1806		DIN 2080, ISO 297, ČSN 220430	110	20	4,54		•	•	•	•						
VK 360	208.046	MK2-(3/8"-16 UNC) *		70	13	0,36	•											
VK 360	208.091	MK3-(M12) *		70	13	0,47	•											
VK 360	208.107	MK3-(1/2"-13 UNC) *		70	13	0,47	•											
VK 360	208.152	MK4-(5/8"-11 UNC) *		70	14,5	0,75	•											
VK 801	208.541	MK4-(M16) *		110	18,5	1,46		•	•	•								
VK 801	208.558	MK4-(5/8"-12 UNC) *		110	18,5	1,46		•	•	•								
VK 801	208.602	MK5-(M20) *		110	18,5	2,22		•	•	•	•							
VK 801	208.619	MK5-(3/4"-10 UNC) *	DIN 69871/A, ISO 297, ČSN 220434	110	18,5	2,22		•	•	•	•							
VK 801	208.671	MK6-(M24) *	110	20	4,53		•	•	•	•								
VK 801	208.688	MK6-(1"-8 UNC) *	110	20	4,53		•	•	•	•								
VK 360	208.183	ISO 30 (M12) DIN 2080		70	9,6	0,4	•											
VK 360	208.190	ISO 30 (1/2"-13 UNC)		70	9,6	0,4	•											
VK 360	208.213	ISO 40 (M16) DIN 2080		70	9,6	0,74	•											
VK 360	208.220	ISO 40 (5/8"-11 UNC)		70	9,6	0,74	•											
VK 360	208.244	ISO 50 (M24) DIN 2080		CAT	70	45,2	3,19	•										
VK 801	208.695	ISO 40-(M16) DIN 2080		MAS - BT	110	13,6	1,35		•	•	•	•						
VK 801	208.701	ISO 40-(5/8"-11 UNC)		110	13,6	1,35		•	•	•	•							
VK 801	208.725	ISO 50-(M24) DIN 2080	110	15,2	2,89		•	•	•	•								
VK 801	208.732	ISO 50-(1"-8 UNC)	110	15,2	2,89		•	•	•	•								
VK 360	208.206	ISO 30 (M12) DIN 69871/A		70	49,1	0,75	•											
VK 360	208.282	CAT 30 (1/2"-13 UNC)		70	44,2	0,75	•											
VK 360	208.237	ISO 40 (M16) DIN 69871/A		70	49,1	1,35	•											
VK 360	208.299	CAT 40 (5/8"-11 UNC)		70	49,1	1,35	•											
VK 360	208.251	ISO 50 (M24) DIN 69871/A		R8	70	49,1	3,05	•										
VK 801	208.718	ISO 40-(M16) DIN 69871/A		110	48,1	1,95		•	•	•	•							
VK 801	208.770	CAT 40-(5/8"-11 UNC)		110	48,1	1,95		•	•	•	•							
VK 801	208.749	ISO 50-(M24) DIN 69871/A	110	65,1	4,78		•	•	•	•								
VK 801	208.787	CAT 50-(1"-8 UNC)	110	65,1	4,78		•	•	•	•								
VK 360	208.268	MAS-BT30 (M12)		70	34,6	0,70	•											
VK 360	208.275	MAS-BT40 (M16)		70	57,0	1,55	•											
VK 801	208.756	MAS-BT40 (M16)		110	43,6	2,12		•	•	•	•							
VK 801	208.763	MAS-BT50 (M24)		110	84,0	5,70		•	•	•	•							
VK 360	208.305	R8 (7/16"-20 UNF)		70	17,6	0,69	•											
VK 800	208.817	R8 (7/16"-20 UNF)		63	17,6	0,64	•											



česky
english
español