

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units – SK 3238.100

Date : Dec 6, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3238.100

created: 06.12.2017 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
With hose-proof hood: IP 56
With fine filter mat or hose-proof hood: IP 54

**Protection category
NEMA:** NEMA 12
With hose-proof hood: NEMA 3
With hose-proof hood: NEMA 3R
With hose-proof hood: NEMA 4
With hose-proof hood: NEMA 4X
With fine filter mat or hose-proof hood: NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Note: With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires on the unit; for all other fan-and-filter units, a screwless spring terminal is used.

Product features

**Air throughput
(unimpeded air flow):** At 50 Hz: 55 m³/h
At 60 Hz: 66 m³/h

**Air throughput with
outlet filter including
standard filter mat
(quantity x order
number, output 50/60
Hz):** 1 x 3238200: 43/50 m³/h
2 x 3238200: 46/56 m³/h

**Rated operating
voltage:** 230 V, 1~, 50 Hz/60 Hz

Dimensions:	Width: 148.5 mm Height: 148.5 mm
Required mounting cut-out:	Width: 124 mm Height: 124 mm
Build depth:	16 mm
Installation depth:	58.5 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -10°C...+55°C
Power consumption Pel:	At 50 Hz: 19 W At 60 Hz: 18 W
Rated current (max.):	At 50 Hz: 0.12 A At 60 Hz: 0.11 A
Miniature circuit-breaker/fuse:	2 A
Noise level:	At 50 Hz: 46 dB(A) At 60 Hz: 49 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor
Packs of:	1 pc(s).
Weight/pack:	0.8 kg
EAN:	4028177651692
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK TopTherm fan-and-filter unit, 55/66 m ³ /h, 230 V, 1~, 50/60 Hz, WH: 148,5x148,5 mm

Approvals

Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity