


Mod.CIG42



REDUCTION RATIO	L	REDUCTION RATIO	L
1/4	32.5	1/212~1/864	52
1/14~1/24	39.2	1/1062~1/3600	59.6
1/49~1/144	45.9		

外形尺寸 APPEARANCE SIZE



GEARED MOTOR TORQUE/SPEED

	減速比 Reduction ratio	1/4	1/14	1/17	1/24	1/49	1/61	1/84	1/104	1/144	1/212	1/294	1/504	1/624	1/720	1/864	1/1062	1/1470	1/2500	1/3000	1/3600
		12V	2.2	6.5	8.1	10	18	18	18	20	20	25	25	30	30	30	30	30	30	30	30
	定額扭力(Kg-cm) Rated torque	1400	405	325	248	120	98	76	63	45	31	24	13.5	10.9	9.5	8.0	6.5	4.6	2.7	2.3	1.9
	定額回轉數(rpm) Rated speed	1.8	5.4	6.6	9.5	16	18	18	20	20	25	25	30	30	30	30	30	30	30	30	30
24V	定額扭力(Kg-cm) Rated torque	1445	420	340	240	122	102	77.5	63	47	31	23.8	13.5	10.9	9.5	8.0	6.5	4.6	2.7	2.3	1.9
	定額回轉數(rpm) Rated speed																				

馬達單體型式 / MOTOR DATA

定額電壓 Rated volt (V)	定額扭力 Rated torque (g-cm)	定額回轉數 Rated speed (rpm)	定額電流 Rated current (mA)	無負荷回轉數 No load speed (rpm)	無負荷電流 No load current (mA)	定額出力 Rated output (W)	重量 Weight (g)
12	700	5700	≤ 5500	7000	≤ 900	41.3	360
24	570	5900	≤ 2100	7000	≤ 500	34.7	360

馬達單體特性圖 / MOTOR CHARACTERISTICS

