

Datenblatt

Steigung

Steigung mm	Anzeige nach einer Umdrehung mm inch	Zulässige max. Drehzahl rpm inch
0,5	0005	600
0,50	0050	200
0,7/5	0007 5	600
1,0	0010	100
1,00	0100	600 200
1,2/5	0012 5	600
1,5	0015	600
1,7/5	0017 5	500
2,0	0020	500 100
2,5	0025	300
3,0	0030	300 600
4,0	0040	200 500
5,0	0050	200 500
6,0	0060	200
7,5	0075	100 200
8,0	0080	100
10,0	0100	100 200
12,0	0120	80



Einbaulage

Ansicht A - horizontal

Ansicht B - vertikal

Ansicht C - frontseitig unten

Ansicht D - frontseitig oben



Bestellbeispiel

Typ	OP3	-	A	-	2,5	-	DX	-	14	-	R	-	P6
Ansicht	A - B - C - D												
Steigung	Anzeigewert nach 1 Umdrehung siehe Tabelle												
Zählrichtung	DX - rechtssteigend SX - linkssteigend												
Wellendurchmesser [mm]	VA - Edelstahl Ø 14 - 12 - 10 - 8 Durchmesser kleiner mit Reduzierbüchse												
Gehäusefarbe	R - orange G - schwarz GR - grau												
Drehmomentstütze	P6 - Ø6 mm P9/10,5 - Ø9-10,5 mm												

Zubehör

Flansch Adapter (FL)



Drehknopf (PM)



Wellenklemmflansch (FL-B)

