

FGDR

Aluminium pressure regulator with built-in filter, to EN 88-1.

Max. inlet pressure 500 mbar. Max. outlet pressure 350 mbar.

Closure control. Suitable for manufactured gas, natural gas, liquefied petroleum gas (LPG), non-aggressive gas and air. Operating temperature range: -15÷+60°C.



Type	Part Number	Connec- tion	Description	Q.ty/ Box	Box/ Carton
FGDR15	009.0220.101	1/2"	With neutral spring 10 - 30 mbar	1	1
FGDR15	009.0220.102	1/2"	With green spring 5 - 15 mbar	1	1
FGDR15	009.0220.103	1/2"	With violet spring 25 - 80 mbar	1	1
FGDR15	009.0220.104	1/2"	With brown spring 70 - 160 mbar	1	1
FGDR15	009.0220.105	1/2"	With blue spring 150 - 280 mbar	1	1
FGDR15	009.0220.106	1/2"	With white spring 270 - 350 mbar	1	1
FGDR20	009.0221.101	3/4"	With neutral spring 10 - 30 mbar	1	1
FGDR20	009.0221.102	3/4"	With green spring 5 - 15 mbar	1	1
FGDR20	009.0221.103	3/4"	With violet spring 25 - 80 mbar	1	1
FGDR20	009.0221.104	3/4"	With brown spring 70 - 160 mbar	1	1
FGDR20	009.0221.105	3/4"	With blue spring 150 - 280 mbar	1	1
FGDR20	009.0221.106	3/4"	With white spring 270 - 350 mbar	1	1
FGDR25	009.0222.101	1"	With neutral spring 10 - 30 mbar	1	1
FGDR25	009.0222.102	1"	With green spring 5 - 15 mbar	1	1
FGDR25	009.0222.103	1"	With violet spring 25 - 80 mbar	1	1
FGDR25	009.0222.104	1"	With brown spring 70 - 160 mbar	1	1
FGDR25	009.0222.105	1"	With blue spring 150 - 280 mbar	1	1
FGDR25	009.0222.106	1"	With white spring 270 - 350 mbar	1	1
FGDR32	009.0223.101	1.1/4"	With neutral spring 10 - 25 mbar	1	1
FGDR32	009.0223.102	1.1/4"	With green spring 5 - 15 mbar	1	1
FGDR32	009.0223.103	1.1/4"	With violet spring 20 - 70 mbar	1	1
FGDR32	009.0223.104	1.1/4"	With brown spring 65 - 130 mbar	1	1
FGDR32	009.0223.106	1.1/4"	With white spring 120 - 250 mbar	1	1
FGDR32	009.0223.107	1.1/4"	With black spring 240 - 350 mbar	1	1
FGDR40	009.0224.101	1.1/2"	With neutral spring 10 - 25 mbar	1	1
FGDR40	009.0224.102	1.1/2"	With green spring 5 - 15 mbar	1	1
FGDR40	009.0224.103	1.1/2"	With violet spring 20 - 70 mbar	1	1
FGDR40	009.0224.104	1.1/2"	With brown spring 65 - 130 mbar	1	1
FGDR40	009.0224.106	1.1/2"	With white spring 120 - 250 mbar	1	1
FGDR40	009.0224.107	1.1/2"	With black spring 240 - 350 mbar	1	1
FGDR50/40	009.0234.101	2"	With neutral spring 10 - 25 mbar	1	1
FGDR50/40	009.0234.102	2"	With green spring 5 - 15 mbar	1	1
FGDR50/40	009.0234.103	2"	With violet spring 20 - 70 mbar	1	1
FGDR50/40	009.0234.104	2"	With brown spring 65 - 130 mbar	1	1
FGDR50/40	009.0234.106	2"	With white spring 120 - 250 mbar	1	1
FGDR50/40	009.0234.107	2"	With black spring 240 - 350 mbar	1	1
FGDR50	009.0225.101	2"	With neutral spring 10 - 35 mbar	1	1
FGDR50	009.0225.102	2"	With green spring 5 - 15 mbar	1	1
FGDR50	009.0225.103	2"	With violet speing 30 - 80 mbar	1	1
FGDR50	009.0225.104	2"	With brown spring 70 - 220 mbar	1	1
FGDR50	009.0225.105	2"	With blue spring 210 - 350 mbar	1	1

Dimensions on page 29