

2408: Powered Hydraulic Bender



The + product:


Bending capacity:

Gas pipes: Ø 3/8" to 4" (nfa 49115 - en 10255).

Locksmith's pipes: Ø 12 à 45 mm.

Bending angle: 0° to 90°.

Description



Electrical hydraulic bender for worksites or prefabrication.

Simple action circuit with spring-loaded piston return.

Supplied in a wooden case with the forms and accessories.

Less effort required for large batches.

Limit switch (option - ref. 240811) to reproduce identical bends.

To identify the different types of cheeks, see next pages.



Tip:

- Use Virax hydraulic ram oil for best protection.
- All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation.
- Use horizontally.

Ref. 240851, Ref. 240852 delivered in two wooden chests

References

Sku	For pipe	Formers	Ram	Туре	kg
240842	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Open Cheeks	93,000
240843	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Sliding Cheeks	87,000

Sku	For pipe	Formers	Ram	Туре	kg
240851	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3 - 3.1/2 - 4"	230 V - n° 3	Hinged Cheeks	303,000
240852	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	230 V - n° 3	Hinged Cheeks	188,000

