



# GAR644C

by Burndy Catalog ID: GAR644C

Prop 65 Notice

Mechanical Grounding Connector, Cable to Rod or Pipe, 8 AWG (Sol)- 4 AWG (Str), 3/8" Pipe, 5/8"-3/4" Rod, #5-#6 Rebar, Bright Dipped.

Features: High Copper Alloy Ground Connector For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Especially Good For Fence Posts, High Copper Alloy Cast Body With DURIUM U-Bolts, Nuts And Lockwashers, Permit Entire Connection To Be Buried In Ground Or Concrete Without Danger Of Corrosion, One-Wrench Installation, UL467 Listed, Acceptable For Direct Burial, Height: 2-7/8 IN, Ground Rod Size: 5/8 - 3/4 IN, Tube (ips) Size: 3/8 IN, Width: 2-1/8 IN, Installation Torque: 240 IN-LB, Rebar Size: #5 (5/8 IN) - #6 (3/4 IN)

# **Product Details**

#### General

ApplicationFor Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Irrect Burial Cable, Fence PostInstallation Torque Recommended in-Ib240 lb-inMaterialCoper AlloyMaterial - HardwareDURIUM™ Silicon BronzePlatedNPlatedSili DippedSub BrandMcCHANICAL CONNECTORTypeGARUBolt Type59JupcSili DipastonMaterial - Marcel AlloySili DipastonMaterial - Material - Marcel AlloySili DipastonMaterial - Material - M		
NaterialCopper AlloyMaterial - HardwareDURIUM™ Silicon BronzePlatedNPlating TypeBright DippedSub BrandMECHANICAL CONNECTORTypeGARU Bolt Type69	Application	
Material - Hardware     DURIUM™ Silicon Bronze       Plated     N       Plating Type     Bright Dipped       Sub Brand     MECHANICAL CONNECTOR       Type     GAR       U Bolt Type     29	Installation Torque Recommended in-Ib	240 lb-in
PlatedNPlating TypeBright DippedSub BrandMECHANICAL CONNECTORTypeGARU Bolt Type69	Material	Copper Alloy
Plating Type     Bright Dipped       Sub Brand     MECHANICAL CONNECTOR       Type     GAR       U Bolt Type     269	Material - Hardware	DURIUM™ Silicon Bronze
Sub Brand     MECHANICAL CONNECTOR       Type     GAR       U Bolt Type     269	Plated	Ν
Type     GAR       U Bolt Type     269	Plating Type	Bright Dipped
U Bolt Type 269	Sub Brand	MECHANICAL CONNECTOR
	Туре	GAR
UPC 781810238004	U Bolt Type	269
	UPC	781810238004
UPC 12 Digit 7818102380044	UPC 12 Digit	7818102380044

# Dimensions

Dimension - B Length inch	1.50 in
Dimension - Height fraction	2-7/8
Dimension - Height inch	2.88 in
Dimension - L Length Overall mm	33 mm
Dimension - Length Overall inch	1.31 in
Dimension - Outside Diameter inch	0.68 in
Dimension - Width fraction	2-1/8 in
Dimension - Width inch	2.06 in
Dimension - Width mm	52 mm

# **Conductor Related**

Conductor - Copper Solid Size	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG
Conductor - Copper Solid Size Range	8 AWG-4 AWG
Conductor - Copper Str Size	9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Str Size Range	9 AWG-4 AWG

Conductor - Copper Tube Std Size	3/8 IPS IPS
Conductor - Copper Tube Std Size Range	3/8 IPS IPS
Conductor - Pipe or Round Tube Size	3/8 in
Conductor - Rebar Size	5 ;6
Conductor - Rebar Size Range	5 -6
Conductor - Rod Size	0.625in - 0.75in
Conductor - Rod Size Range	5/8 in-3/4 in
Conductor Type	<ul> <li>CU C Solid-Size</li> <li>CU C Str-Size</li> <li>CU Tube Std-Size</li> <li>Rod-Size</li> </ul>

# Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

# Logistics

Minimum Pack Quantity	1

# For further technical assistance, please contact us

# **BURNDY Headquarters**

47 East Industrial Park Drive Manchester, New Hampshire 03109

#### **Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)